

# Test Report



test report, No.:	18. marts 2021		by:	TDL/JSJ	
client:					
<b>Product</b>					
name:	Potato flour		chemical:	N/A	
application:	flour		temp.	20	dgC
characteristica:	abrassive		not corrosive		
	not hygroscopic		not soluble		
	dusty		not sticky		
size [mm]:	min.		max.		test
water content:	spec.	N/A	%	test	N/A %
bulk density:	spec.	N/A	kg/dm <sup>3</sup>	test	0,22 kg/dm <sup>3</sup>
slip angel:	static	-	°	dynamic	- °
<b>Equipment</b>					
elevator, type:	110				
inlet control:	Drum Feeder				
bucket, type:	FRB		meterial:	PP-Glass	
bucket, volume:	9,5	liter	nos/mtr:	3,3	

Test	bucket filling			chain	capacity	
	gram	liter	degree		m/min	m <sup>3</sup> /h
@ ambient temp.						
#1		0,00	0%		0,0	0,0
#2		0,00	0%		0,0	0,0
#3		0,00	0%		0,0	0,0
#4		0,00	0%		0,0	0,0
#5		0,00	0%		0,0	0,0
#6 max		0,00	0%		0,0	0,0

<b>Comments</b>	
-----------------	--